









ACCIAIO LAMINATO a CALDO
Cod.: 418000 "TONDI"
Cod.: 954012 "QUADRI"

DIMENS. mm	PESO Kg/mm		DIMENS. mm	PESO Kg/mm		DIMENS. mm	PESO Kg/mm		DIMENS. mm	PESO Kg/mm	
											
3	0,055	-	12	0,888	1,130	21	2,720	3,460	36	7,990	10,200
4	0,099	0,125	13	1,040	1,330	22	2,980	3,800	38	8,900	11,300
5	0,154	0,196	14	1,210	1,540	24	3,550	4,520	40	9,860	12,600
6	0,222	0,283	15	1,390	1,770	25	3,850	4,910	42	10,900	13,800
7	0,302	0,385	16	1,580	2,010	27	4,490	5,720	45	12,500	15,900
8	0,395	0,502	17	1,780	2,270	28	4,830	6,150	50	15,400	19,600
9	0,499	0,636	18	2,000	2,540	30	5,550	7,070			
10	0,617	0,785	19	2,230	2,830	32	6,310	8,040			
11	0,746	0,950	20	2,470	3,140	35	7,550	9,620			

Cod. 950

ACCIAIO LAMINATO a CALDO
"TRAVI"
 Travi NP profilo normale

H = Altezza B = Larghezza S = Spessore A = Spessore asta

INP da	H mm	B mm	S mm	A mm	Sezione cm ²	Peso Kg/m
80	80	42	5,9	3,9	7,57	5,95
100	100	50	6,8	4,5	10,60	8,32
120	120	58	7,7	5,1	14,20	11,15
140	140	66	8,6	5,7	18,20	14,37
160	160	74	9,5	6,3	22,80	17,90
180	180	82	10,4	6,9	27,90	21,90
200	200	90	11,3	7,5	33,40	26,30
220	220	98	12,2	8,1	39,50	31,09
240	240	106	13,1	8,7	46,10	36,19
260	260	113	14,1	9,4	53,30	41,92
280	280	119	15,2	10,1	61,00	47,96
300	300	125	16,2	10,8	69,00	54,24

